



## CERTIFICATE

---

Solarif Insurance (i.e. Solar Insurance B.V.) declares, after a thorough risk assessment of amongst others the production lines, financial strength, environmental and labor conditions, that the modules mentioned below from the **Vikram Solar Pvt. Ltd.** factory located at Special Economic Zone (SEZ) Sector 2 FALTA, 24 Parganas (South) 743504, West Bengal, India are approved.

The certificate is valid from **17 December 2015** until **17 December 2016** and as long as the company is not insolvent.

This certificate enables clients who use the approved inverters to insure their PV installation – as an optional cover on the operational Solar PV Insurance – against damages arising from or caused by an inherent defect.

This insurance is exclusively available through Solarif.

For more information or a quotation, please contact us by email [midoffice@solarif.com](mailto:midoffice@solarif.com) or visit us at [www.solarif.com](http://www.solarif.com).

On behalf of Solarif Insurance

Date: **4 April 2016**

Harry Wolkenfelt  
Chief Executive Officer



Certificate no. **CRT-VISO-20160404-0069**



# SOLARIF

INSURANCE

<b>APPROVED POLY-CRYSTALLINE MODULES</b>				
<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>	<i>Euro. Efficiency</i>	<i>Number and size of cell</i>
Eldora VSP.60.AAA.03	240-265	0,+5W	14.75-16.29	10x6
Eldora VSP.60.AAA.03	240-260	0,+5W	14.91-16.15	10x6
Eldora VSPB.60.AAA.03	240-260	0,+5W	14.75-15.98	10x6
Eldora VSPBB.60.AAA.03	240-260	0,+5W	14.75-15.98	10x6
Eldora VSP.60.AAA.03	270-280	0,+5W	16.6-17.21	10x6
Eldora VSP.54.AAA.03	205-250	0,+5W	13.9-16.95	9x6
Eldora VSPB.54.AAA.03	205-250	0,+5W	13.9-16.95	9x6
Eldora VSPBB.54.AAA.03	205-250	0,+5W	13.9-16.95	9x6
Eldora VSP.48.AAA.03	180-220	0,+5W	13.7-16.75	8x6
Eldora VSPB.48.AAA.03	180-220	0,+5W	13.7-16.75	8x6
Eldora VSPBB.48.AAA.03	180-220	0,+5W	13.7-16.75	8x6
Eldora VSP.36.AAA.03	135-165	0,+5W	13.43-16.42	6x6
Eldora VSPB.36.AAA.03	135-165	0,+5W	13.43-16.42	6x6
Eldora VSPBB.36.AAA.03	135-165	0,+5W	13.43-16.42	6x6
Eldora VSP.60.AAA.03.01	225-260	0,+5W	13.98-16.15	10x6
Eldora VSP.60.AAA.03.01	240-260	0,+5W	14.75-15.98	10x6
Eldora VSP.72.AAA.03	290-315	0,+5W	14.95-16.23	12x6
Eldora VSPB.72.AAA.03	290-315	0,+5W	14.95-16.23	12x6
Eldora VSP.72.AAA.03	280-315	0,+5W	14.58-16.41	12x6

Certificate no. **CRT-VISO-20160404-0069**